

APT Session 7: Compilers



Laurence
Tratt



Software Development Team
2015-12-02

What to expect from this session

- 1 Building a compiler.

Prerequisites

- 1 Have the programming language of your choice (e.g. Java, Python) installed and running on your computer.
- 2 For Java: clone and compile Sam White's [parser](#).
- 3 For Python: download my [simple parser](#).
- 4 Use Sam White's [stack visualizer](#).
- 5 (Optionally, but highly recommended) use Sam White's [go.py](#) which allows you to pipe output straight from your compiler to the stack visualizer e.g.:

```
python3 compiler.py ex4.h11 | python3 go.py
```

Compilers (1)

- In previous sessions we've written: an interpreter for a stack machine; and a parser for simple languages.

Compilers (1)

- In previous sessions we've written: an interpreter for a stack machine; and a parser for simple languages.
- A compiler is the link we need between the two to takes in 'human readable' programs and convert them to stack format.

Compilers (1)

- In previous sessions we've written: an interpreter for a stack machine; and a parser for simple languages.
- A compiler is the link we need between the two to takes in 'human readable' programs and convert them to stack format.
- Compilers for dynamically typed languages are simple. [Statically typed languages' compilers, especially if they heavily optimise code, are superficially more complex, though they're still conceptually simple.]

Compilers (1)

- In previous sessions we've written: an interpreter for a stack machine; and a parser for simple languages.
- A compiler is the link we need between the two to takes in 'human readable' programs and convert them to stack format.
- Compilers for dynamically typed languages are simple. [Statically typed languages' compilers, especially if they heavily optimise code, are superficially more complex, though they're still conceptually simple.]
- Our starting grammar:

```
Stmt ::= Assign | While | Print
Assign ::= ID = Expr ;
Expr ::= INT + Expr | INT - Expr | INT < Expr
      | INT > Expr | INT
While ::= WHILE Expr { stmt* }
Print ::= PRINT Expr ;
```

- Python and Java tree-creating parsers are provided for this grammar.

Compilers (2)


- The transformation our compiler needs is fairly simple. For example `print 2 + 3;` should be transformed to:

```
INT 2
INT 3
ADD
PRINT
EXIT
```

- The trick is to break this transformation into phases. The first is parsing (which we did in the last session). The second is code generation (which we'll do today). The (optional) third is optimisation (which we don't need).

Parse trees

- Last time we wrote a 'yes/no' parser. More commonly we want a parse tree as output.
- For example the parse tree for `x = 2 + 3;` is:




which we will write as `assign("x", binop("+", int(2), int(3)))`.

- The program `print 2;` is transformed to the parse tree `print(int(2))` etc.

Parse trees

- Last time we wrote a 'yes/no' parser. More commonly we want a parse tree as output.
- For example the parse tree for `x = 2 + 3;` is:



which we will write as `assign("x", binop("+", int(2), int(3)))`.

- The program `print 2;` is transformed to the parse tree `print(int(2))` etc.

Exercises:

- 1 Write the program `print 2;` into a file `ex1.hll` and parse it.

Traversing over a parse tree

- A compiler is a translator of parse tree nodes to code.

Traversing over a parse tree

- A compiler is a translator of parse tree nodes to code.
- To make life easier, parse tree edges are labelled. So a `print` node has an `exp`, an `int` node has a `val` and so on.

Traversing over a parse tree

- A compiler is a translator of parse tree nodes to code.
- To make life easier, parse tree edges are labelled. So a `print` node has an `exp`, an `int` node has a `val` and so on.
- We iterate over the tree, gradually converting it to stack-based instructions.
- For a `print` node: process the `exp` then add a `PRINT` instruction.
For an `int`: simply create an `INT` instruction.

Traversing over a parse tree

- A compiler is a translator of parse tree nodes to code.
 - To make life easier, parse tree edges are labelled. So a `print` node has an `exp`, an `int` node has a `val` and so on.
 - We iterate over the tree, gradually converting it to stack-based instructions.
 - For a `print` node: process the `exp` then add a `PRINT` instruction. For an `int`: simply create an `INT` instruction.
-

Exercises:

- 1 Write a simple compiler which reads a file in, parses it, converts `ex1.hll` to a stack-based format and prints the output to `stdout`. Initially you only need to handle parse trees of the form `print (int (n))` (where `n` is an integer). Run the output in the stack visualiser.

More sophisticated traversal

- Compilers mostly do a *preorder* traversal: process the node; process the Left Hand Side (LHS) of the node (all the way); process the Right Hand Side (RHS) of the node (all the way).
- For a BINOP (e.g. add/sub/etc.) node: process the `lhs` then the `rhs` then emit the appropriate binop instruction.

More sophisticated traversal

- Compilers mostly do a *preorder* traversal: process the node; process the Left Hand Side (LHS) of the node (all the way); process the Right Hand Side (RHS) of the node (all the way).
- For a `BINOP` (e.g. add/sub/etc.) node: process the `lhs` then the `rhs` then emit the appropriate binop instruction.
- For each node type `X`, we need a function `t_X` which to process it. We also need a function `preorder` which takes in an arbitrary node and dispatches to the appropriate `t_` function.

More sophisticated traversal

- Compilers mostly do a *preorder* traversal: process the node; process the Left Hand Side (LHS) of the node (all the way); process the Right Hand Side (RHS) of the node (all the way).
 - For a BINOP (e.g. add/sub/etc.) node: process the `lhs` then the `rhs` then emit the appropriate binop instruction.
 - For each node type X , we need a function `t_ X` which to process it. We also need a function `preorder` which takes in an arbitrary node and dispatches to the appropriate `t_ X` function.
-

Exercises:

- 1 Adjust your previous compiler to be a class with traversal functions `t_ X` and a general `preorder` function.
- 2 Write the program `print 2 + 3` into a file `ex2.hll`.
- 3 Add a binop traversal function (which need only cope with '+').
- 4 Run the output in the stack visualiser.

Variables

- Working only with the stack is frustrating; we want a heap. Variables are named parts of the heap.
- The stack machine has two variable instructions:

```
VAR_SET x  
VAR_LOOKUP y
```

VAR_SET sets the variable `x` to the (popped) top of the stack.

VAR_LOOKUP looks up a variable `y` and pushes it onto the stack.

Variables

- Working only with the stack is frustrating; we want a heap. Variables are named parts of the heap.
- The stack machine has two variable instructions:

```
VAR_SET x  
VAR_LOOKUP y
```

VAR_SET sets the variable `x` to the (popped) top of the stack.
VAR_LOOKUP looks up a variable `y` and pushes it onto the stack.

Exercises:

- 1 Write the program `x=2; y=2+3; print x+y;` into a file `ex3.hll`.
- 2 Add variable traversal functions.
- 3 Run the output in the stack visualiser.

Conditionals

- The stack machine defines `LESS_THAN`, `MORE_THAN`, and `EQUALS` which do:

```
rhs = stack.pop()
lhs = stack.pop()
stack.push(lhs op rhs)
```

where `op` is `<`, `>`, or `==`. 0 is pushed for false, 1 for true.

Conditionals

- The stack machine defines `LESS_THAN`, `MORE_THAN`, and `EQUALS` which do:

```
rhs = stack.pop()
lhs = stack.pop()
stack.push(lhs op rhs)
```

where `op` is `<`, `>`, or `==`. 0 is pushed for false, 1 for true.

Exercises:

- 1 Write the program `print 2 < 3;` into a file `ex4.hll`.
- 2 Add conditional traversal functions.
- 3 Run the output in the stack visualiser.

Loops

- A `while` loop has a condition and a body. While the condition doesn't evaluate to 0, the body is executed.

Loops

- A `while` loop has a condition and a body. While the condition doesn't evaluate to 0, the body is executed.
-

Exercises:

1 Write the program

```
i = 0;
while i < 10 {
    print i;
    i = i + 1;
}
```

into a file `ex5.hll`.

- 2 Add a while loop traversal function. You will need labels and jumps.
- 3 Run the output in the stack visualiser.

Post-session exercises

Try these (no particular order):

- Extend the parser to handle functions and update the compiler accordingly.
- Read [how difficult is it to write a compiler?](#) in light of your experiences.